

# Overview MC Technologies Terminals

Article	Article-No.	Frequency MHz	GPRS Class	Temperature Range	EDGE	JAVA	GPS	UMTS	Interfaces	1. RS232	2. RS232	RS485	USB	GPIO
AC75 Terminal	MC1213876-Terminal	850/900/1800/1900	12	-40°C +85°C	x	x			x				O	
AC65i Terminal	MC1213879-Terminal	850/900/1800/1900	12	-40°C +85°C		x			x					
EU3 Terminal	MC1213650-Terminal	GSM900/1800 HSDPA 900/2100	10	-40°C +85°C	x			x	x*				x*	
HC25 USB Terminal	MC1213825-Terminal	GSM850/900/1800/1900 HSDPA 850/1900/2100	12	-30°C +75°C	x			x	x*				x*	
HC25 TM Terminal	MC1213825-TM	GSM850/900/1800/1900 HSDPA 850/1900/2100	12	-30°C +75°C	x			x	x*				x*	
HC25 GPS Terminal	MC1213825-Term-GPS	GSM850/900/1800/1900 HSDPA 850/1900/2100	12	-30°C +75°C	x		x	x	x*				x*	
MC88 Terminal	MC1213888-Terminal	850/900/1800/1900	12	-40°C +85°C		x			x					
MC88i Terminal		850/900/1800/1900	12	-40°C +85°C		x			x				x	
MC55i Terminal	MC1213649-Terminal	850/900/1800/1900	10	-40°C +70°C					x					
MC55i TM Terminal	MC1213649-TM	850/900/1800/1900	10	-40°C +70°C					x					
MC66-E Terminal	MC1213652-Terminal	900/1800	8	-40°C +85°C					x					
MC66-W Terminal	MC1213653-Terminal	850/900/1800/1900	10	-40°C +85°C					x					
MC75i Terminal	MC1213675-Terminal	850/900/1800/1900	12	-40°C +75°C	x				x					
MC75i TM Terminal	MC1213675-TM	850/900/1800/1900	12	-40°C +75°C	x				x					
MC75i USB Terminal	MC1213675-USB-232	850/900/1800/1900	12	-40°C +75°C	x				x				x	
TC65i JavaTerm	MC1213673-Terminal	850/900/1800/1900	12	-40°C +75°C		x			x					
TC65i TM Terminal	MC1213673-TM	850/900/1800/1900	12	-40°C +75°C		x			x	x				
TC65i USB Terminal	MC1213673-USB-232	850/900/1800/1900	12	-40°C +75°C		x			x				x	
TC65i RS485 Terminal	MC1213673-485-Term	850/900/1800/1900	12	-40°C +75°C		x			x			x		
TC65i GPIO Terminal	MC1213673-T-GPIO	850/900/1800/1900	12	-40°C +75°C		x			x					x
TC65i GPIO USB Terminal	MC1213673-T-GPIO-USB	850/900/1800/1900	12	-40°C +75°C		x			x				x	x
TC63i Terminal	MC1213672-Terminal	850/900/1800/1900	12	-40°C +75°C					x					
TC63i TM Terminal	MC1213672-TM	850/900/1800/1900	12	-40°C +75°C					x					
TC63i USB Terminal	MC1213672-USB-232	850/900/1800/1900	12	-40°C +75°C					x				x	
XT75 Terminal	MC1213881-Terminal	850/900/1800/1900	12	-30°C +85°C	x	x	x		x					
XT75 USB Terminal	MC1213881-USB-232	850/900/1800/1900	12	-30°C +85°C	x	x	x		x				x	
XT75 GPIO Terminal	MC1213881-Term-GPIO	850/900/1800/1900	12	-30°C +85°C	x	x	x		x					x
XT75 GPIO USB Terminal	MC1213881-T-GPIO-USB	850/900/1800/1900	12	-30°C +85°C	x	x	x		x				x	x
XT65 Terminal	MC1213882-Terminal	850/900/1800/1900	12	-30°C +85°C		x	x		x					
XT65 USB Terminal	MC1213882-USB-232	850/900/1800/1900	12	-30°C +85°C		x	x		x				x	
XT65 GPIO Terminal	MC1213882-Term-GPIO	850/900/1800/1900	12	-30°C +85°C		x	x		x					x
XT65 GPIO USB Terminal	MC1213882-T-GPIO-USB	850/900/1800/1900	12	-30°C +85°C		x	x		x				x	x
TRM3 TERMINAL	MC1213649-R	GSM-R/900/1800/1900	10	-25°C +70°C					x					

Standard interfaces: antenna GSM = FME / GPS = SMA; Power Supply RJ12 (Western-Plug), SIM Card Reader

\* = optional RS232 or USB

O = optional